



MATERIAL SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BUEHLER POWDERED MOLD RELEASE
 IDENTIFICATION NUMBER: 20-3048
 PRODUCT USE/CLASS: Mold release/lubricant

SUPPLIER:
 BUEHLER, a division of Illinois Tool Works Inc.
 41 WAUKEGAN ROAD
 LAKE BLUFF, IL 60044

EMERGENCY: 800-424-9300
 INFORMATION: 847-295-6500
 PREPARER: Technical Department, 847-295-6500
 PREPARE DATE: 03/23/09, 23 March 2009

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT%
No Hazardous Materials are Contained in this Product			

ITEM	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL – CEILING	COMPANY TLV-TWA	SKIN
No Hazardous Materials are Contained in this Product						

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Vapors from heated material may be irritating. Contact with heated material can cause thermal burns.

ACUTE EFFECTS – EYE CONTACT: Exposure to hot material may cause thermal burns.

ACUTE EFFECTS - SKIN CONTACT: Contact with product at elevated temperatures can result in thermal burns.

ACUTE EFFECTS – INHALATION: Vapors and/or aerosols formed at elevated temperatures can be irritating.

ACUTE EFFECTS - INGESTION: Not expected to present a hazard in normal industrial use.

CHRONIC OVEREXPOSURE EFFECTS: None known

OTHER INFORMATION: No information.

PRIMARY ROUTE(S) OF ENTRY: Not applicable.

SECTION 4 – FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT: For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing as the damaged flesh can be easily torn.

INHALATION: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop.

INGESTION: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

NOTES TO PHYSICIAN: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: 570 F (PENSKEY-MARTENS C.C.)

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: No data

EXTINGUISHING MEDIA: CO₂, DRY CHEMICAL, FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: Finely divided dust in air may present explosion hazard. Prevent dust buildup.

SPECIAL FIREFIGHTING PROCEDURES: Treat as petroleum fire. Wear appropriate approved protective equipment. Avoid directing water stream directly into flame; it may cause frothing with subsequent spread of flame.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Reclaim clean material. Contaminated material should be swept or shoveled into appropriate waste container and disposed of in accordance with applicable federal, state and local regulations.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Minimize dust generation and accumulation. Avoid breathing vapors from heated material.

STORAGE: Keep away from heat and flame.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: General ventilation usually adequate.

RESPIRATORY PROTECTION: None normally required under general ventilation.

SKIN PROTECTION: Clean clothing to cover skin. Thermal gloves when handling hot material.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: Accessible eye wash and safety shower.

HYGIENIC PRACTICES: Follow good general industrial safety practices during use. Do not smoke or eat during use.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE:	N.A.	VAPOR DENSITY:	Is heavier than air
ODOR:	Odorless	ODOR THRESHOLD:	N.A.
APPEARANCE:	Tan powder	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H ₂ O:	Insoluble		
FREEZE POINT:	No data	SPECIFIC GRAVITY:	0.8093
VAPOR PRESSURE:	N.A.	pH @ 0.0%:	N.A.
PHYSICAL STATE:	Solid	VISCOSITY:	N.A.
COEFFICIENT OF WATER/OIL DISTRIBUTION:	No data		

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 – STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No information.

INCOMPATIBILITY: No information.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon. Aromatic and aliphatic hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 – TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL TEST DATA: No information.

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Material as sold may be disposed of in landfill if local regulations permit. If material becomes contaminated, follow disposal instructions for contaminant.

SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not regulated	
DOT TECHNICAL NAME: N.A.	
DOT HAZARD CLASS: N.A.	HAZARD SUBCLASS: N.A.
DOT UN/NA CLASS: N.A.	PACKAGING GROUP: N.A.
	RESP. GUIDE PAGE:
INTERNATIONAL SHIPPING NAME: Not regulated	
INTERNATIONAL ID NUMBER: N.A.	
IMDG CLASS (1°, 2°): N.A.	IMDG PAGE NUMBER: N.A.
IMDG EMS: N.A.	IATA CLASS (1°, 2°): N.A.
ADR ITEM NO.: N.A.	ADR TREMCARD: N.A.
SUPPLEMENTAL INFORMATION: No information	

SECTION 15 – REGULATORY INFORMATION

OSHA: Non-hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA – SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED, AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:

SARA SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 AND 40 CFR PART 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCE CONTROL ACT: THE CHEMICAL SUBSTANCES IN THIS PRODUCT ARE ON THE TSCA SECTION 8 INVENTORY. THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

----- CHEMICAL NAME ----- CAS NUMBER

No components found.

NEW JERSEY RIGHT-TO-KNOW: THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP 5 COMPONENTS IN THIS PRODUCT:

----- CHEMICAL NAME ----- CAS NUMBER

Carnauba wax 8015-86-9

PENNSYLVANIA RIGHT-TO-KNOW: THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%:

----- CHEMICAL NAME ----- CAS NUMBER

Carnauba wax 8015-86-9

CALIFORNIA PROPOSITION 65: No Proposition 65 chemicals known to exist in this product.

CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: NOT REGULATED

COMPONENT RCRA CLASSIFICATIONS: NOT REGULATED

COMPONENT RCRA CODES: No information.

CERCLA RQ VALUE (MINIMUM): None known

SECTION 16 – OTHER INFORMATION

HMIS RATINGS

HEALTH: 0

FLAMMABILITY: 1

REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 05/22/06; 22 MAY 06

REASON FOR REVISION: Administrative change for new format.

VOLATILE ORGANIC COMPOUNDS: 0 grams/ltr

LEGEND:

N.A. – NO INFORMATION

N.E. – NOT ESTABLISHED

N.D. – NOT DETERMINED

ABBREVIATIONS: ACGIH = AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS; OSHA = OCCUPATIONAL HEALTH AND SAFETY ADMINISTRATION; TLV-TWA = THRESHOLD LIMIT VALUE – TIME WEIGHTED AVERAGE (8 HOURS); STEL = SHORT-TERM EXPOSURE LIMIT (15 MINUTES); C = CEILING VALUE; PEL = PERMISSIBLE EXPOSURE LIMIT

DISCLAIMER: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED IN THIS MSDS IS ACCURATE OR IS OBTAINED FROM SOURCES BELIEVED TO BE ACCURATE. HOWEVER, NO LIABILITY, EXPRESSED OR IMPLIED, IS ASSUMED FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. BUYER ASSUMES LIABILITY IN ITS USE OF THE MATERIAL.