



## MATERIAL SAFETY DATA SHEET

### SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BUEHLER DRESSING STICK  
 IDENTIFICATION NUMBER: 10-4000, 11-1190, -1290, -2490, -2495, 15-6190, 40-4510  
 PRODUCT USE/CLASS: Abrasive

SUPPLIER:  
 BUEHLER, a division of Illinois Tool Works Inc.  
 41 WAUKEGAN ROAD  
 LAKE BLUFF, IL 60044

EMERGENCY: 800-424-9300  
 INFORMATION: 847-295-6500  
 PREPARER: Technical Department, 847-295-6500  
 PREPARE DATE: 03/23/09, 23 March 2009

### SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT%			
01	Sulfur	7704-34-9	1.0-5.0			
02	Cobalt Aluminate	1333-88-6	< 0.1			
03	Aluminum oxide	1344-28-1	60.0-100.0			
04	Silicon Carbide	409-21-2	60.0-100.0			
ITEM	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL – CEILING	COMPANY TLV-TWA	SKIN
01	10 mg/m <sup>3</sup>	N.E.	10 mg/m <sup>3</sup>	N.E.	N.E.	NO
02	0.02 mg/m <sup>3</sup>	N.E.	0.05 mg/m <sup>3</sup>	N.E.	N.E.	NO
03	10 mg/m <sup>3</sup>	N.E.	15 mg/m <sup>3</sup>	N.E.	N.E.	NO
04	10 mg/m <sup>3</sup>	N.E.	15 mg/m <sup>3</sup>	N.E.	N.E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Harmful if inhaled or swallowed. Dust irritating to respiratory tract. Suspect cancer hazard.

ACUTE EFFECTS – EYE CONTACT: Mechanical irritant. Contact may cause tearing and redness.

ACUTE EFFECTS - SKIN CONTACT: Not expected to present a hazard in normal industrial use. Mechanical irritant. Prolonged contact may cause skin abrasion.

ACUTE EFFECTS – INHALATION: Dust or vapors may be slightly irritating to respiratory tract. Prolonged inhalation may be harmful.

ACUTE EFFECTS - INGESTION: May cause nausea and vomiting.

CHRONIC OVEREXPOSURE EFFECTS: \*Ingestion of significant amounts of cobalt may cause damage to the blood, heart, thyroid, or pancreas. \*This product contains a substance or substances that have been listed as an animal carcinogen by IARC.

OTHER INFORMATION: Not Applicable.

PRIMARY ROUTE(S) OF ENTRY: INHALATION

### SECTION 4 – FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

INHALATION: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN: Not Applicable.

### SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: N.A.

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.A.

EXTINGUISHING MEDIA: N.A.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Not Applicable.

SPECIAL FIREFIGHTING PROCEDURES: Does not burn.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: N.A.

## SECTION 7 – HANDLING AND STORAGE

HANDLING: Minimize dust generation and accumulation.

STORAGE: Not Applicable.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: General ventilation usually adequate.

RESPIRATORY PROTECTION: If exposure levels are unknown, if levels exceed TLV/PEL, or if effects occur, use NIOSH-approved dust/mist respirator in accordance with applicable health and safety regulations and manufacturer's recommendations.

SKIN PROTECTION: Clean clothing to cover skin.

EYE PROTECTION: Not Applicable.

OTHER PROTECTIVE EQUIPMENT: Not Applicable.

HYGIENIC PRACTICES: Follow good general industrial safety practices during use.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE:	N.A.	VAPOR DENSITY:	Is heavier than air
ODOR:	None	ODOR THRESHOLD:	N.A.
APPEARANCE:	Solid stick	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H <sub>2</sub> O:	Insoluble		
FREEZE POINT:	N.A.	SPECIFIC GRAVITY:	3.2898
VAPOR PRESSURE:	N.A.	pH @ 0.0%:	N.A.
PHYSICAL STATE:	N.A.	VISCOSITY:	N.A.
COEFFICIENT OF WATER/OIL DISTRIBUTION:	N.A.		

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

## SECTION 10 – STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Not Applicable.

INCOMPATIBILITY: Strong chlorates, bromates, liquid chlorine, concentrated oxygen, sodium hypochlorite, calcium hypochlorite.

HAZARDOUS DECOMPOSITION PRODUCTS: Not Applicable.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

## SECTION 11 – TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

## SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL TEST DATA: Not Available

## SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Material as sold may be disposed of in landfill if local regulations permit. If material becomes contaminated, follow disposal instructions for contaminant.

## SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not regulated for transport

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A.

HAZARD SUBCLASS: N.A.

DOT UN/NA CLASS: N.A.

PACKAGING GROUP: N.A.

RESP. GUIDE PAGE: N.A.

INTERNATIONAL SHIPPING NAME: Not regulated for transport

INTERNATIONAL ID NUMBER: N.A.

IMDG CLASS (1°, 2°): N.A.

IMDG PAGE NUMBER: N.A.

IMDG EMS: N.A.

IATA CLASS (1°, 2°): N.A.

ADR ITEM NO.: N.A.

ADR TREMCARD: N.A.

SUPPLEMENTAL INFORMATION: Not Applicable.

## SECTION 15 – REGULATORY INFORMATION

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA – SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED, AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: NONE

SARA SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 AND 40 CFR PART 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCE CONTROL ACT: THE CHEMICAL SUBSTANCES IN THIS PRODUCT ARE ON THE TSCA SECTION 8 INVENTORY. THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

----- CHEMICAL NAME ----- CAS NUMBER

No components found.

NEW JERSEY RIGHT-TO-KNOW: THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP 5 COMPONENTS IN THIS PRODUCT:

----- CHEMICAL NAME ----- CAS NUMBER

Fused amorphous silicon dioxide 60676-86-0

PENNSYLVANIA RIGHT-TO-KNOW: THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%: none

CALIFORNIA PROPOSTION 65: No Proposition 65 chemicals known to exist in this product

CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: NONE

COMPONENT RCRA CLASSIFICATIONS: Not regulated

COMPONENT RCRA CODES: Not Applicable.

CERCLA RQ VALUE (MINIMUM): None known

## SECTION 16 – OTHER INFORMATION

### HMIS RATINGS

HEALTH: 1

FLAMMABILITY: 0

REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 5/20/06; 20 MAY 06

REASON FOR REVISION: Administrative change for new format.

VOLATILE ORGANIC COMPOUNDS: 0 grams/ltr

### LEGEND:

N.A. – NO INFORMATION

N.E. – NOT ESTABLISHED

N.D. – NOT DETERMINED

ABBREVIATIONS: ACGIH = AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS; OSHA = OCCUPATIONAL HEALTH AND SAFETY ADMINISTRATION; TLV-TWA = THRESHOLD LIMIT VALUE – TIME WEIGHTED AVERAGE (8 HOURS); STEL = SHORT-TERM EXPOSURE LIMIT (15 MINUTES); C = CEILING VALUE; PEL = PERMISSIBLE EXPOSURE LIMIT

DISCLAIMER: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED IN THIS MSDS IS ACCURATE OR IS OBTAINED FROM SOURCES BELIEVED TO BE ACCURATE. HOWEVER, NO LIABILITY, EXPRESSED OR IMPLIED, IS ASSUMED FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. BUYER ASSUMES LIABILITY IN ITS USE OF THE MATERIAL.