



MATERIAL SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BUEHLER BLACK PIGMENT FOR CASTABLE MOUNTS
 IDENTIFICATION NUMBER: 20-8502
 PRODUCT USE/CLASS: Pigment

SUPPLIER:
 BUEHLER, a division of Illinois Tool Works Inc.
 41 WAUKEGAN ROAD
 LAKE BLUFF, IL 60044

EMERGENCY: 800-424-9300
 INFORMATION: 847-295-6500
 PREPARER: Technical Department, 847-295-6500
 PREPARE DATE: 03/23/09, 23 March 2009

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT%			
01	Epoxy resin	TRADE SECRET	60.0-100.0			
02	Carbon Black	1333-86-4	10.0-30.0			
ITEM	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL – CEILING	COMPANY TLV-TWA	SKIN
01	N.E.	N.E.	N.E.	N.E.	N.E.	NO
02	3.5 mg/m ³	N.E.	3.5 mg/m ³	N.E.	2.5 mg/m ³	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Causes skin and eye irritation. May cause allergic skin reaction.

ACUTE EFFECTS – EYE CONTACT: Moderately irritating to the eyes.

ACUTE EFFECTS - SKIN CONTACT: May cause allergic skin reaction. Moderate irritant. Prolonged contact may cause dermatitis.

ACUTE EFFECTS – INHALATION: Dust or vapors may be slightly irritating to respiratory tract.

ACUTE EFFECTS - INGESTION: Irritating to mouth, throat and stomach, with nausea.

CHRONIC OVEREXPOSURE EFFECTS: *Preexisting pulmonary and dermatological disorders may be aggravated by exposure to hazardous components. *Repeated and prolonged inhalation of graphite or carbon dusts may cause pulmonary fibrosis, emphysema, and pneumoconiosis. No exposure to free respirable carbon is anticipated during normal mix and cure of this product; however, dust may be released by grinding, cutting, or machining of cure material. The severity of the pulmonary effects is greatly influenced by the presence of other harmful mineral dusts, most notably crystalline silica.

OTHER INFORMATION: No information.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT, EYE CONTACT

SECTION 4 – FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN CONTACT: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INHALATION: If symptoms occur, remove to fresh air. Medical personnel may administer oxygen if breathing is difficult. Seek medical attention if symptoms persist.

INGESTION: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

NOTES TO PHYSICIAN: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: 480 F

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: No data

EXTINGUISHING MEDIA: CO₂, DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture or explode (due to pressure build-up) when exposed to extreme heat. Irritating and/or toxic gases or fumes may be generated by thermal decomposition or combustion.

SPECIAL FIREFIGHTING PROCEDURES: Use NIOSH-approved self-contained breathing apparatus and full protective clothing. Use water to cool exposed containers. Water stream directed into fire may cause frothing with subsequent spread of flame.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Reclaim clean material. Wear gloves and goggles during cleanup. Sprinkle area with inert absorbent, such as clay or sand. Sweep and wipe up residual with rags or paper towels. Dispose of rags and absorbent in a manner which protects against further exposure. Wash spill area with mild detergent solution.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid contact with skin and eyes. FOR INDUSTRIAL USE ONLY.

STORAGE: KEEP OUT OF THE REACH OF CHILDREN.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: General industrial ventilation usually adequate.

RESPIRATORY PROTECTION: None normally required under general ventilation. If TLV/PEL is exceeded, if use is performed in a poorly-ventilated space, or if inhalation effects occur, use NIOSH-approved vapor cartridge respirator in accordance with applicable health and safety regulations and manufacturer's recommendations.

SKIN PROTECTION: Clean clothing to cover skin. Butyl rubber gloves. Nitrile gloves. Supported PVA gloves.

EYE PROTECTION: Chemical splash goggles.

OTHER PROTECTIVE EQUIPMENT: Accessible eye wash and safety shower.

HYGIENIC PRACTICES: Follow good general industrial safety practices during use. Do not smoke or eat during use. DO NOT reuse empty containers without commercial clean or recondition. Follow all MSDS/label precautions even after container is emptied.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE:	500 - 500 F	VAPOR DENSITY:	Is heavier than air
ODOR:	No appreciable	ODOR THRESHOLD:	No data
APPEARANCE:	Black	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H ₂ O:	Negligible		
FREEZE POINT:	No data	SPECIFIC GRAVITY:	1.1042
VAPOR PRESSURE:	Very low	pH @ 0.0%:	N/A
PHYSICAL STATE:	Liquid	VISCOSITY:	Medium
COEFFICIENT OF WATER/OIL DISTRIBUTION:	No data		

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 – STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No information.

INCOMPATIBILITY: Strong Lewis or mineral acids. Strong bases or oxidants. Reaction with amines and mercaptans in large amounts or under uncontrolled conditions releases considerable heat and may release acrid fumes.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon. Various hydrocarbons. Irritating aldehydes and ketones. Aldehydes and acids from incomplete combustion. Phenolic compounds.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 – TOXICOLOGICAL PROPERTIES

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----

Epoxy resin
Carbon Black

----- LD50 -----

Oral-rat=>11 g/kg
Oral-rat=>8 g/kg

----- LC50 -----

No deaths/satd air
No information

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL TEST DATA: No information.

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all current federal, state, and local regulations regarding health and disposal for appropriate disposal procedures. When cured, product is non-hazardous, and may be placed in industrial or municipal landfill if local regulations permit. Product is not considered a "hazardous waste" per federal RCRA regulations if disposed of "as sold."

SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not regulated

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A.

DOT UN/NA CLASS: N.A.

HAZARD SUBCLASS: N.A.

PACKAGING GROUP: N.A.

RESP. GUIDE PAGE:

INTERNATIONAL SHIPPING NAME: Not regulated

INTERNATIONAL ID NUMBER: N.A.

IMDG CLASS (1°, 2°): N.A.

IMDG EMS: N.A.

IMDG PAGE NUMBER: N.A.

IATA CLASS (1°, 2°): N.A.

SECTION 15 – REGULATORY INFORMATION

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA – SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED, AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: IMMEDIATE HEALTH HAZARD
CHRONIC HEALTH HAZARD

SARA SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 AND 40 CFR PART 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCE CONTROL ACT: THE CHEMICAL SUBSTANCES IN THIS PRODUCT ARE ON THE TSCA SECTION 8 INVENTORY. THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

----- CHEMICAL NAME ----- CAS NUMBER

No components found.

NEW JERSEY RIGHT-TO-KNOW: THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP 5 COMPONENTS IN THIS PRODUCT: None

PENNSYLVANIA RIGHT-TO-KNOW: THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%: None

CALIFORNIA PROPOSTION 65: None

CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: D2B

COMPONENT RCRA CLASSIFICATIONS: Not regulated

COMPONENT RCRA CODES: No information.

CERCLA RQ VALUE (MINIMUM): None known

SECTION 16 – OTHER INFORMATION

HMIS RATINGS

HEALTH: 2

FLAMMABILITY: 1

REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 02/20/09; 20 Feb 2009

REASON FOR REVISION: Administrative change for new format.

VOLATILE ORGANIC COMPOUNDS: 0 grams/ltr

LEGEND:

N.A. – NO INFORMATION

N.E. – NOT ESTABLISHED

N.D. – NOT DETERMINED

ABBREVIATIONS: ACGIH = AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS; OSHA = OCCUPATIONAL HEALTH AND SAFETY ADMINISTRATION; TLV-TWA = THRESHOLD LIMIT VALUE – TIME WEIGHTED AVERAGE (8 HOURS); STEL = SHORT-TERM EXPOSURE LIMIT (15 MINUTES); C = CEILING VALUE; PEL = PERMISSIBLE EXPOSURE LIMIT

DISCLAIMER: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED IN THIS MSDS IS ACCURATE OR IS OBTAINED FROM SOURCES BELIEVED TO BE ACCURATE. HOWEVER, NO LIABILITY, EXPRESSED OR IMPLIED, IS ASSUMED FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. BUYER ASSUMES LIABILITY IN ITS USE OF THE MATERIAL.