

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 204 C

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: No data

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Irritating and/or toxic gases or fumes may be generated by thermal decomposition or combustion.

SPECIAL FIREFIGHTING PROCEDURES: Treat as petroleum fire. Wear appropriate approved protective equipment. Avoid directing water stream directly into flame; it may cause frothing with subsequent spread of flame.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Reclaim clean material. Wash spill area with soap and water. Prevent washings from entering waterways. Place contaminated material in covered waste container and dispose of in accordance with local and national regulations.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid contact with eyes, skin, and clothing. Follow good general industrial safety practices during use and handling. FOR INDUSTRIAL USE ONLY.

STORAGE: KEEP OUT OF THE REACH OF CHILDREN.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: General ventilation usually adequate.

RESPIRATORY PROTECTION: None normally required under good general industrial ventilation.

SKIN PROTECTION: Clean clothing to cover skin. Rubber or synthetic gloves.

EYE PROTECTION: Safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Eye wash.

HYGIENIC PRACTICES: DO NOT reuse empty containers.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : N.A. VAPOR DENSITY : Is heavier than air
ODOR : No appreciable ODOR THRESHOLD : No data
APPEARANCE : Brown EVAPORATION RATE: Is slower than Butyl Acetate
SOLUBILITY IN H2O : Negligible
FREEZE POINT : No data SPECIFIC GRAVITY: 1.1407
VAPOR PRESSURE : Negligible pH @ 100.0 % : N/A
PHYSICAL STATE : Liquid VISCOSITY : Medium
COEFFICIENT OF WATER/OIL DISTRIBUTION: No data
(See Section 16 for abbreviation legend)

Continued on Page 3)


```

=====
SECTION 15 - REGULATORY INFORMATION
=====

```

CHiP SUPPLY LABEL RISK PHRASES: (R36/38) Irritating to eyes and skin. (R43) May cause sensitisation by skin contact. (R51) Toxic to aquatic organisms. (R53) May cause long-term adverse effects in the aquatic environment.

CHiP SUPPLY LABEL SAFETY PHRASES: (S28) After contact with skin, wash immediately with plenty of water. (S37/39) Wear suitable gloves and eye/face protection. (S61) Avoid release to the environment. Refer to special instructions/safety data sheet. Contains epoxy constituents. See information supplied by the manufacturer. For industrial or professional use ONLY.

CHiP SUPPLY LABEL SYMBOLS: Irritant, Xi; Danger to the Environment, N

```

=====
SECTION 16 - OTHER INFORMATION
=====

```

PREVIOUS MSDS REVISION DATE: none
REASON FOR REVISION: new product

VOLATILE ORGANIC COMPOUNDS (VOCS): 0 grams/ltr (calculated)

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

ABBREVIATIONS: Administrative Revision Date: Reason for administrative revision: ACGIH = American Conference of Governmental Industrial Hygienists; UK = United Kingdom; REL = Recommended Exposure Limit; MAK = Maximale Arbetisplatzkonzentration (Maximum Concentration in the Workplace); TLV-TWA = Threshold Limit Value-Time Weighted Average (8 hours); STEL = Short-Term Exposure Limit (15 minutes); C = Ceiling Value; PEL = Permissible Exposure Limit

DISCLAIMER: To the best of our knowledge, the information contained in this MSDS is accurate or is obtained from sources believed to be accurate. However, no liability, expressed or implied, is assumed for the accuracy or completeness of the information contained herein. Buyer assumes liability in its use of the material.

```

=====
=====
<END OF MSDS>

```