



MATERIAL SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BUEHLER EpoxiCure NC Resin
 IDENTIFICATION NUMBER: 20-8150-02, 20-8150-001
 PRODUCT USE/CLASS: Epoxy resin

SUPPLIER:
 BUEHLER, a division of Illinois Tool Works Inc.
 41 WAUKEGAN ROAD
 LAKE BLUFF, IL 60044

EMERGENCY: 800-424-9300
 INFORMATION: 847-295-6500
 PREPARER: Technical Department, 847-295-6500
 PREPARE DATE: 03/23/09, 23 March 2009

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT%			
01	Alkyl glycidyl ether	TRADE SECRET	10.0-30.0			
02	Neopentyl Glycol Diglycidyl Ether	17557-23-2	10.0-30.0			
03	Epoxy Resin	TRADE SECRET	60.0-100.0			
ITEM	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL – CEILING	COMPANY TLV-TWA	SKIN
01	N.E.	N.E.	N.E.	N.E.	N.E.	NO
02	N.E.	N.E.	N.E.	N.E.	N.E.	NO
03	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Harmful if swallowed. Causes skin irritation. May cause allergic skin reaction. Prolonged contact may cause eye injury.

ACUTE EFFECTS – EYE CONTACT: Contact may cause injury to eye tissue if not removed promptly.

ACUTE EFFECTS - SKIN CONTACT: Contact causes skin irritation. Repeated or prolonged contact may cause sensitization. Moderate irritant. Prolonged contact may cause dermatitis.

ACUTE EFFECTS – INHALATION: Liquid aspirated into lungs may cause serious injury or death. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

ACUTE EFFECTS - INGESTION: May cause nausea and vomiting. Substance may be harmful if swallowed.

CHRONIC OVEREXPOSURE EFFECTS: *Preexisting pulmonary and dermatological disorders may be aggravated by exposure to hazardous components. *Neopentyl glycol diglycidyl ether was found to be carcinogenic in skin painting tests on mice. Mutagenic "in-vitro." *Contains a substance or substances shown to be mutagenic in in-vitro (test tube) assays.

OTHER INFORMATION: No information.

PRIMARY ROUTE(S) OF ENTRY: INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION

SECTION 4 – FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN CONTACT: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INHALATION: If symptoms occur, remove to fresh air. Medical personnel may administer oxygen if breathing is difficult. Seek medical attention if symptoms persist.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: 220 F (PENSKY-MARTENS C.C.)

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: NO

EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CO₂, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture or explode (due to pressure build-up) when exposed to extreme heat. Irritating and/or toxic gases or fumes may be generated by thermal decomposition or combustion.

SPECIAL FIREFIGHTING PROCEDURES: Use NIOSH-approved self-contained breathing apparatus and full protective clothing. Use water to cool exposed containers. Water stream directed into fire may cause frothing with subsequent spread of flame.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Reclaim clean material. Wear appropriate protective equipment during cleanup. Absorb with inert material, such as clay. Sweep or shovel into loosely-covered waste container and remove to appropriate waste area. Dispose of in accordance with federal, state, and local regulations. Harmful to aquatic organisms. Prevent entry into drains and/or waterways.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid contact with eyes, skin, and clothing. FOR INDUSTRIAL USE ONLY.

STORAGE: Store in a cool dry place. Keep container closed when not in use.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust as needed to control vapor or dust levels to below lowest component TLV.

RESPIRATORY PROTECTION: If TLV/PEL is exceeded, if use is performed in a poorly-ventilated space, or if inhalation effects occur, use NIOSH-approved vapor cartridge respirator in accordance with applicable health and safety regulations and manufacturer's recommendations.

SKIN PROTECTION: Natural rubber gloves. Neoprene gloves.

EYE PROTECTION: Chemical splash goggles.

OTHER PROTECTIVE EQUIPMENT: Accessible eye wash and safety shower.

HYGIENIC PRACTICES: Follow good general industrial safety practices during use. Do not smoke or eat during use. DO NOT reuse empty containers without commercial clean or recondition.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE:	392 - 580 F	VAPOR DENSITY:	Is heavier than air
ODOR:	Sweet	ODOR THRESHOLD:	No data
APPEARANCE:	Clear thin yellow	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H ₂ O:	Negligible		
FREEZE POINT:	No data	SPECIFIC GRAVITY:	1.1299
VAPOR PRESSURE:	<0.1 mm@20 degC	pH @ 0.0%:	N.A.
PHYSICAL STATE:	Liquid	VISCOSITY:	Low
COEFFICIENT OF WATER/OIL DISTRIBUTION:	No data		

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 – STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Prolonged exposure to heat.

INCOMPATIBILITY: Strong Lewis or mineral acids. Strong bases or oxidants. Reaction with amines and mercaptans in large amounts or under uncontrolled conditions releases considerable heat and may release acrid fumes.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon. Aldehydes and acids from incomplete combustion. Phenolic compounds.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 – TOXICOLOGICAL PROPERTIES

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----

Alkyl glycidyl ether

Neopentyl Glycol Diglycidyl Ether

Bisphenol-F epoxy resin

----- LD50 -----

Derm-rbt >4.5 g/kg

oral(rat)4.5g/kg

Oral-rat=> 2 g/kg

----- LC50 -----

rat >1.5mg/l/4Hr

No information

no data

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL TEST DATA: No information.

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all current federal, state, and local regulations regarding health and disposal for appropriate disposal procedures. When cured, product is non-hazardous, and may be placed in industrial or municipal landfill if local regulations permit.

SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not regulated for transport

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A.

DOT UN/NA CLASS: N.A.

HAZARD SUBCLASS: N.A.

PACKAGING GROUP: N.A.

RESP. GUIDE PAGE:

INTERNATIONAL SHIPPING NAME: Not regulated as a dangerous good for transport

INTERNATIONAL ID NUMBER: N.A.

IMDG CLASS (1°, 2°): N.A.

IMDG EMS: N.A.

IMDG PAGE NUMBER: N.A.

IATA CLASS (1°, 2°): N.A.

SECTION 15 – REGULATORY INFORMATION

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA – SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED, AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: IMMEDIATE HEALTH HAZARD

SARA SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 AND 40 CFR PART 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCE CONTROL ACT: THE CHEMICAL SUBSTANCES IN THIS PRODUCT ARE ON THE TSCA SECTION 8 INVENTORY. THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

----- CHEMICAL NAME ----- CAS NUMBER

Alkyl glycidyl ether TRADE SECRET

Neopentyl Glycol Diglycidyl Ether 17557-23-2

NEW JERSEY RIGHT-TO-KNOW: THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP 5 COMPONENTS IN THIS PRODUCT:

----- CHEMICAL NAME ----- CAS NUMBER

No non-hazardous materials are among the top five ingredients.

PENNSYLVANIA RIGHT-TO-KNOW: THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%:

----- CHEMICAL NAME ----- CAS NUMBER

No non-hazardous ingredients are present at greater than 3%.

CALIFORNIA PROPOSTION 65: No Proposition 65 chemicals known to exist in this product.

CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: D2B

COMPONENT RCRA CLASSIFICATIONS: Not regulated

COMPONENT RCRA CODES: No information.

CERCLA RQ VALUE (MINIMUM): None known

SECTION 16 – OTHER INFORMATION

HMIS RATINGS

HEALTH: 2

FLAMMABILITY: 1

REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 08/29/05

REASON FOR REVISION: Administrative change for new format.

VOLATILE ORGANIC COMPOUNDS: 0 grams/ltr

LEGEND:

N.A. – NO INFORMATION

N.E. – NOT ESTABLISHED

N.D. – NOT DETERMINED

ABBREVIATIONS: ACGIH = AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS; OSHA = OCCUPATIONAL HEALTH AND SAFETY ADMINISTRATION; TLV-TWA = THRESHOLD LIMIT VALUE – TIME WEIGHTED AVERAGE (8 HOURS); STEL = SHORT-TERM EXPOSURE LIMIT (15 MINUTES); C = CEILING VALUE; PEL = PERMISSIBLE EXPOSURE LIMIT

DISCLAIMER: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED IN THIS MSDS IS ACCURATE OR IS OBTAINED FROM SOURCES BELIEVED TO BE ACCURATE. HOWEVER, NO LIABILITY, EXPRESSED OR IMPLIED, IS ASSUMED FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. BUYER ASSUMES LIABILITY IN ITS USE OF THE MATERIAL.